

The OPL 9724 is equipped with bluetooth interface and offers secure wireless communication. This model is equipped with 3 keys and a graphical display, integrated barcode laser scanner, 128 kB memory, a real-time clock and supplied with a rechargeable battery.

Data collector

OPL 9724

Barcode data collector with Bluetooth interface



Features

- Bluetooth interface
- SPP and DUN profiles supported
- Three buttons operation
- LCD display
- Small size and light weight
- Flash ROM and RAM memory

Benefits

- Enables wireless communication
- Allows easy connection to mobile phones and PDA's
- Plain and simple navigation
- Clear overview
- Easy to carry
- Provides program and data storage

Cabled

Wireless

Stationary

OEM

OPTICON
always scanning for new ID's

Specifications

OPL 9724 Barcode data collector with Bluetooth interface

Electrical specifications

Main battery pack	Li-Ion rechargeable 3,7 V / nom. 600 mAh
Backup battery	Lithium rechargeable 3,5 mAh
Backup battery operating time	> 1 week backup
Battery management	When battery is low the data collector switches off automatically.
Charging method	The main battery in data collector will be charged through the cradle. The backup battery will be charged by the main battery.

Optical specifications

Light source	650 nm visible laser diode
Scan method	vibrating mirror
Target indicator	100 scans/sec
Decode rate	100 decodes/sec
Reading angle	effective 44°
Reading pitch angle	+8 - +50° / -8 - -50°
Reading skew angle	± 35°
Reading rotation angle	20°
Reading width	45 - 320 mm, depending on reading distance and bar code label resolution
Min. Resolution at PCS 0.9	0.15 mm (6mil)
Min. PCS value	0.45
Depth of field	60 - 300 mm (UPC PCS0.9, resolution 1.00), 35 - 210 mm (UPC PCS0.9, resolution 0.5), 35 - 120 mm (UPC PCS0.9, resolution 0.25), 35 - 70 mm (UPC PCS0.9, resolution 0.15)

Wireless communication specifications

Frequency	2.4 GHz
Profile	Bluetooth: GAP, SPP, DUN
Operation range	up to 10 meters, depending on environment characteristics
Connection mode	1 to 1
Operation mode	master, slave
Low power mode	park, sniff, hold
Security mode	authentication, encryption

Identification

Supported barcode symbologies	Codabar - Code 39 - Code 93 - Code 128 - EAN-8 incl. +2,+5 - EAN-13 incl. +2,+5 - EAN-128 - IATA - Industrial 2of5 - Interleaved 2of5 - Italian Pharmaceutical - MSI/Plessey - UK/Plessey - Telepen - TriOptic - UPC-A incl. +2,+5 - UPC-E incl. +2,+5
Future extension	Chinese Post - Codabar incl. ABC and CX - ISBN - ISSN

Functionality

Trigger mode	manual by trigger key
Memory FlashROM	512 kB (O/S and program)
Memory RAM	128 kB (data storage)
Microprocessor	16-bit
Real time clock	Quartz RTC, time and date programmable, leap year handling, (accuracy +/- 60 sec./month)
Display	112x64 Pixels graphic LCD
Character fonts	min. 4 lines x 14 characters, max. 10 lines x 18 characters
Keyboard	3 keys total (user definable)
Keyboard function keys	2 function keys
Programming	Functionality is provided by user application.
Interface IrDA	supported
Interface Bluetooth	supported (see wireless communication specifications)
Transmission speed IrDA	baudrate: 2400 - 115200 bps

Environmental specifications

Temperature in operation	-5 - +40 °C
Temperature in storage	-20 - +60 °C
Humidity in operation	20 - 80 % (non condensing)
Humidity in storage	20 - 90 % (non condensing)
Ambient fluorescent light rejection	3.000 lux max
Ambient white light rejection	3.000 lux max
Ambient direct sun light rejection	50.000 lux max
Shock vibration test	12 - 100 Hz with 2G for 1 hour
Protection (dust and moisture, IEC529)	IP 54

Physical specifications

Dimensions	(l x w x d) 125 x 42 x 19 mm
Case material	ABS
Weight body	< 85 g

Regulatory

Laser safety class	IEC 825, Class I laserproduct
EMC	EN 55022, EN 55024
R&TTE	EN 300-328, ETS 300-826

CRD 972X Cradle for OPL 972X

Electrical specifications

Voltage requirement	6 V DC, +/- 10%
---------------------	-----------------

Physical specifications

Dimensions	(h x w x d) (excl. cable and operation space) single cradle: excl. collector 65 x 72 x 97 mm, incl. collector 122 x 72 x 97 mm, multi cradle: excl. collector 65 x 310 x 97 mm, incl. collector 122 x 310 x 97 mm
Case material	ABS
Weight body	single cradle: ca. 85 g, multi cradle: ca. 335 g

Models

charging	CRD-9722-CHARGER
communication/charging	CRD-9723-RU
communication/charging+RS485	CRD-9725+CABLE
communication/charging+slotcharger	CRD-9725+CABLE
multiple charging / single communication (5/1)	CRD-9723R&U1
multiple charging / multiple communication (5/5)	CRD-9723R&U5

Regulatory

EMC	EN 55022, EN 55024
-----	--------------------