

COMPACT 30 mm SLOT SENSORS



- *Infrared LED emission*
- *Sensitivity trimmer adjustment*
- *Elevated switching frequency*
- *Metal housing with wide slot*

SR31 SERIES

The **SR31** series is composed of slot sensors with infrared LED emission, distinguished by an elevated 10 kHz switching frequency and by a sturdy and compact metal housing.

The detection sensitivity is adjusted by means of a trimmer. The dark/light operating mode is configured according to the connection.


The series includes M8 connector versions with NPN output, or PNP output; cable versions present both NPN/PNP outputs.

The **SR31** sensors have a 30 mm wide and 42 mm deep slot. These sensors are suitable for detecting opaque labels on a transparent support, to control material presence and continuity, to detect synchronism pulses on toothed or holed wheels, or as on-off edge guide.


TECHNICAL DATA

Power supply:	10 ... 30 Vdc, reverse polarity protection
Consumption:	50 mA max.
Light emission:	infrared LED 880 nm
Resolution:	2 mm
Slot width:	30 mm
Slot depth:	42 mm
Detection point depth:	12 mm
Setting:	multi-turn sensitivity trimmer
Indicators:	red OUTPUT LED
Output type:	NPN or PNP (connector vers.) NPN and PNP (cable vers.) Rpull-down/up 10 k Ω
Saturation voltage:	0.8 V max. (NPN vers.) 2 V max. (PNP vers.)
Output current:	200 mA max., short-circuit protection
Response time:	50 μ s max.
Switching frequency:	10 kHz max.
Operating mode:	dark/light configurable
Connection:	4-pole M8 connector 2 m \varnothing 5 mm cable
Electrical protection:	class 1
Mechanical protection:	IP60
Housing material:	ZAMA
Lens material:	glass
Weight:	100 g max.
Operating temperature:	-10 ... +60°C
Storage temperature:	-20 ... +70°C
Reference standard:	EN 60947-5-2
Certifications:	CE

CONNECTIONS



DIMENSIONS





MODELS

MODEL	CONNECTION	OUTPUT	CODE N°
SR31	cable	NPN/PNP	S970830000
SR31-0	M8 connector	NPN	S970830101
SR31-1	M8 connector	PNP	S970830201

ACCESSORIES

Please refer to *Sensor Accessories*

Distributed by:

HEADQUARTERS

DATASENSOR SpA

via Lavino, 265 - 40050 Monte San Pietro, BO - Italy

Tel. +39 051/6765611 • Fax +39 051/6759324

www.datasensor.com • e-mail info@datasensor.com

Datasensor SpA endeavours to continuously improve and renew its products; for this reason the technical data and contents of this catalogue may undergo variations without prior notice. For correct installation and use Datasensor SpA can guarantee only the data indicated in the instruction manual supplied with the products.

SLOT SENSORS