



# HT 200e

## The Stand-alone Label Specialist - The SATO HT 200e

The innovative, stand-alone HT 200e printer is the perfect low-cost solution, for both retail and industrial applications. With ready-made formats, automatic calculations and touch of a button printing, this printer is fast and very user-friendly.

- ✓ *Direct Thermal*
- ✓ *Stand alone or Online*
- ✓ *Automatic Calculations*
- ✓ *Optional Battery Pack*
- ✓ *Easy Label Loading*
- ✓ *Simple To Use*
- ✓ *Easy To Program*


**Stand-alone** - There is no need for a PC with the HT 200e, this printer is stand-alone, printing labels at a touch of a button.

**Portable** - The HT 200e can be run directly from the mains or from the rechargeable battery. The carry handle also means the printer is easy to transport.

**Simple to use** - easy label loading, ready-made formats and automatic calculations make the HT 200e very user-friendly.

**Easy to program** - For those wishing to design their own formats, programming is very straightforward and the memory large enough to store your personal designs.

**Applications** - retail price marking, medical/pharmaceutical labelling, bakeries, cosmetics, stock control, item identification.





## HT 200e

<b>Printing Method</b>	Direct Thermal
<b>Print Resolution</b>	8 dots/mm (203 dpi)
<b>Print Speed</b>	Up to 60 mm/sec (2.3 ips ) Battery Operated Up to 80 mm/sec (3.1 ips) AC Adapter
<b>Max. Print Width</b>	48 mm (1.89")
<b>Max. Print Length</b>	96 mm (3.78")
<b>Media Size</b>	Min. 28 mm (1.1") W x 16 mm (0.63") L Max. 51 mm (2") W x 103 mm (4") L
<b>Dimensions</b>	132 mm W x 230 mm D x 151 mm H (5.2" W x 9.06" D x 5.94" H)
<b>Weight</b>	2.4 kg (5.3 lb) with Battery Pack 2.5 kg (5.5 lb) with Power Supply

### Features:

- Auto Power off (5 min)
- Calendar (Standard)
- Back lit LCD  
(16 Characters x 3 Lines)

### Memory:

512K Bytes SRAM  
2 MB SRAM Card (optional)

### Processor:

32-Bit RISC, 60 Mhz

### Media:

Caliper: 0.14-0.19mm  
(5.5 - 7.48 MIL)  
Core Diameter: 26.5 mm (1")  
Max. Roll O.D.: 75 mm (2.95")

### Sensing:

Transmissive Sensor for Gaps  
Reflective Sensor for I-Marks

### Interface Connection:

RS232C Serial Interface  
Scanner (RS232C)

### Barcode Symbolologies:

UPC-A/-E, EAN-8/13, Code39, Code128,  
I2/5

### Barcode:

2:1, 2.5:1, 3:1 ratio;  
barcode height 1 to 240 dots

### Human Readable Fonts:

8 fonts including 4 useful POP characters.  
Code Pages 858 and 852

### Rotation:

Font: 0°, 90°, 180°, 270°  
Barcode: 0°, 180°

### Self Check Function:

Paper End; Cover Open; Test Print;  
Battery Level Check; Head Check

### AC Power:

AC 230V +/-10%; Voltage + 8.4 V  
Consumption: Max. 71VA 43W

### Options:

Battery Pack & Charger, SRAM Card  
(2MB), Touch or Pen Scanner, Label  
Rewinder