

The OPL 9727 is equipped with three keys. The bar code data collector is standard equipped with integrated barcode laser scanner, 128 kB memory, a real-time clock and supplied with a rechargeable battery.

Data collector

# OPL 9727

Barcode data collector with tripple key and IrDA interface



## Features

- Plain and simple navigation
- Easy to carry
- Provides program storage
- Provides data collection storage
- IrDA interface
- IP 54 Protection

## Benefits

- Three buttons operation
- Small size and light weight
- Flash ROM memory
- RAM memory
- Optical data transmission to cradle
- Enables outdoor use

Cabled

**Wireless**

Stationary

OEM

**OPTICON**  
always scanning for new ID's

# Specifications

## OPL 9727 Barcode data collector with tripple key and IrDA interface

### Electrical specifications

Main battery pack	Li-Ion rechargeable 3,7 V / nom. 600 mAh
Main battery pack operating time	When making every 5 seconds 1 scan with 1 sec laserbeam on and 0.2 sec. green LED on and 0.2 sec. buzzer on, operating time is: approx. 200 hours
Main battery condition	Different operation conditions affect the operating time
Backup battery	Lithium rechargeable 3,5 mAh
Backup battery operating time	> 1 week backup
Battery management	When battery is low the data collector switches off automatically.
Charging method	The main battery in data collector will be charged through the cradle. The backup battery will be charged by the main battery.

### Optical specifications

Light source	650 nm visible laser diode
Scan method	vibrating mirror
Target indicator	100 scans/sec
Decode rate	100 decodes/sec
Reading angle	effective 44°
Reading pitch angle	+8 - +50° / -8 - -50°
Reading skew angle	± 25°
Reading rotation angle	20°
Reading width	45 - 320 mm, depending on reading distance and bar code label resolution
Min. Resolution at PCS 0.9	0.15 mm (6mil)
Min. PCS value	0.45
Depth of field	60 - 300 mm (UPC PCS0.9, resolution 1.00), 35 - 210 mm (UPC PCS0.9, resolution 0.5), 35 - 120 mm (UPC PCS0.9, resolution 0.25), 35 - 70 mm (UPC PCS0.9, resolution 0.15)

### Identification

Supported barcode symbologies	Codabar - Code 39 - Code 39 Full ASCII - Code 93 - Code 128 - EAN-8 incl. +2,+5 - EAN-13 incl. +2,+5 - EAN-128 - IATA - Industrial 2of5 - Interleaved 2of5 - Italian Pharmaceutical - MSI/Plessey - UK/Plessey - Telepen - TriOptic - UPC-A incl. +2,+5 - UPC-E incl. +2,+5
Future extension	Chinese Post - Codabar incl. ABC and CX - ISBN - ISSN

### Functionality

Trigger mode	manual by trigger key
Memory FlashROM	512 kB (O/S and program)
Memory RAM	128 kB (data storage) / optional 512 KB
Microprocessor	16-bit
Real time clock	Quartz RTC, time and date programmable, leap year handling, (accuracy +/- 60 sec./month)
Keyboard	3 keys total (user definable)
Keyboard function keys	2 function keys
Programming	Functionality is provided by user application.
Transmission speed IrDA	baudrate: 2400 - 115200 bps

### Environmental specifications

Temperature in operation	-5 - +40 °C
Temperature in storage	-20 - +60 °C
Humidity in operation	20 - 80 % (non condensing)
Humidity in storage	20 - 90 % (non condensing)
Ambient fluorescent light rejection	3.000 lux max
Ambient white light rejection	3.000 lux max
Ambient direct sun light rejection	50.000 lux max
Shock drop test	1.5 m drop onto concrete surface
Shock vibration test	12 - 100 Hz with 2G for 1 hour

### Physical specifications

Dimensions	(l x w x d) 125 x 42 x 19 mm
Case material	ABS
Weight body	< 85 g

### Regulatory

Laser safety class	IEC 825, Class I laserproduct
EMC	EN 55022, EN 55024

## CRD 972X Cradle for OPL 972X

### Electrical specifications

Voltage requirement	6 V DC, +/- 10%
---------------------	-----------------

### Physical specifications

Dimensions	(h x w x d) (excl. cable and operation space) single cradle: excl. collector 65 x 72 x 97 mm, incl. collector 122 x 72 x 97 mm, multi cradle: excl. collector 65 x 310 x 97 mm, incl. collector 122 x 310 x 97 mm
Case material	ABS
Weight body	single cradle: ca. 85 g, multi cradle: ca. 335 g

### Models

charging	CRD-9722-CHARGER
communication/charging	CRD-9723-RU
communication/charging+RS485	CRD-9725+CABLE
communication/charging+slotcharger	CRD-9725+CABLE
multiple charging / single communication (5/1)	CRD-9723R&U1
multiple charging / multiple communication (5/5)	CRD-9723R&U5

### Regulatory

EMC	EN 55022, EN 55024
-----	--------------------